

CINEFLEX 512

The Cineflex 512 is the ideal stabilized platform option for smaller broadcast payloads. With 6-axes of movement via VectorSteering™ in an extremely small package, this gimbal weighs 36 lbs (without payload) making it lightweight and versatile.

► SYSTEM FEATURES

- Advanced fiber optic gyro-stabilization
- VectorSteering™ 6-axes of movement in a 5-axis gimbal
 - Stabilized look down (no gimbal lock) in a smaller, lighter package
- Geo-pointing with moving map interface option
- Continuous digital zoom through 10x (camera dependent)
- Isolated electronics eliminates video noise
- Fully upgradeable as gimbal, camera, and lens technologies evolve
- No auxiliary junction unit required
- Stabilized or steerable horizon with in-flight automatic calibration
- No ITAR or EAR export restrictions
- Ships as excess baggage (<70lbs/32kg per case)
- MIL-STD-810F power filters with reverse polarity protection
- Engineered/Manufactured to DO-160G standards - not certified
- Platform designed for both standard and inverted use
- Wireless capability option
- Metadata outputs (lens, camera, & GPS functions)
- Remote controlled optical filter system
- Electro-mechanical gimbal stow mechanism
- Compatible with existing air and ground mounts
- Standard 1-year warranty and 24/7/365 customer service



▶ SYSTEM SPECIFICATIONS

Gimbal Performance

VectorSteering™ offers 6-axes of movement in a 5-axis gimbal - gyrostabilized
Azimuth: 360° continuous
Elevation: 35° to -210° from horizontal
Roll: > +/- 90° (steerable/stabilized)
Gimbal slew rate: 0-130°/second depending on gearbox
Max operational airspeed: variable depending on gearbox

Interface

Control: RS-232, RS-422, or ethernet

Electrical

VIN: 18-33 VDC
Power: 15 amps max draw at 28 VDC

Dimensions

Gimbal width: 13.8 inches (351 mm)
Gimbal height: 17.7 inches (450 mm)
Snout length: 0-6 inches (0-152 mm)
Cable set length: 20 feet (standard set)

Weight

Platform: 36 lbs (16.3 kg) with payload
Hand Control Unit: 7 lbs (3.2 kg)
Auxiliary Junction Unit: payload specific
Cable Set: 8 lbs (3.6 kg)

Environmental

Operating temperature: -4° to +122° F (-20° to +50° C)
Sealed system for airborne/ground/marine applications

Camera/Lens Payload Options*

Sony HDC-P1, HDC-P43 & HDC-P50
Ikegami HDL-F4000 Low-Light
Grass Valley LDX Compact HD/4K
Panasonic AK-UB300 4K
Canon ME20F-SH Low-light
NEC NC-H1200S
*Other cameras available upon request

Interchangeable Lens Options**

Canon HJ/CJ Series
Fujinon HA/4K Series
**Other lenses available upon request

Helicopter/Airplane Mount Availability

AS 350/355 Bell 206/206L/407 Bell 505
EC-120 Robinson R44/R66 Cessna 172/206
(Compatible with various other aircraft)

Vehicle/Marine Mount Configurations

Arm Mounts Mitchell Mount
Various other mount types from many manufacturers

Specifications are subject to change.